

Wideband RF Isolator

Electrical Specifications

Frequency Band	146-226 MHz
Bandwidth	Single Frequency
Input Power (Max.)	150 W
Reflected Power (Max.)	75 W
Isolation Ant-Tx (Min. / Typ.)	65 / 75 dB
Isolator Stage	Dual
Load Termination	30/75 W
Insertion Loss (Max.)	0.80 dB
Return Loss (Min.)	28+ dB
Impedance (Nom.)	50 Ω
RF Connectors	N Female

Mechanical Specifications

Finish	Nickel
Overall Size (HxWxD)	2.5" x 6.77" x 7.3" (64 x 172 x 185 mm)
Net Weight	3.7 lbs (1.7 kg)
Ship Weight	5 lbs (2.3 kg)

Environmental Specifications

Operating Temp. Range	32 to 122 °F (0 to +50 °C)
-----------------------	----------------------------



EMR Corp W-Series (Wideband) line of ferrite Isolators/Circulators have excellent narrow band as well as broadband specifications. These isolators maintain low insertion loss with stable operation while providing excellent isolation at 30+ dB for single and 65+ dB for dual units. Wider bandwidths help to facilitate stocking requiring fewer SKU Nos for inventory making the W-Series an ideal choice for distributors.

Product Features

- Available from 30 MHz to 1.3 GHz Bands
- Wider Bandwidths available with changes to specifications.

