

## Receiver Multicoupler

### Electrical Specifications


Frequency Band	300-512 MHz
Number of Channels	8
Passband Range	3-10 MHz
Number of Resonators	5
Isolation Rx-Rx (Min.)	23+ dB
Amplifier Gain (Typ.)	+30 dB
Amplifier Bias Voltage	13.6 VDC
Amplifier Noise Figure	2.8 dB
Amplifier Current Draw	200 mA
Amplifier Type	Bipolar
1dB Comp. Point	+21 dBm
System NF (Typ.)	5.0 dB
System Voltage	100-240 VAC
VSWR @ Resonance (Max.)	1.25:1
Impedance (Nom.)	50 $\Omega$
RF Connectors (I/O)	N Female

### Mechanical Specifications

Finish	Gray Panel
Rack Mount	19" EIA
Rack Units	3 RU
Overall Size (HxWxD)	5.25" x 19" x 10" (133 x 483 x 254 mm)
Ship Weight	12 lbs (5.4 kg)

### Environmental Specifications

Operating Temp. Range	-22 to 140 °F (-30 to +60 °C)
-----------------------	-------------------------------



EMR Receiver Multicouplers allow several receivers to share a common antenna. These units include a preselector, amplifier, power supply and power divider which effectively amplify a filtered band of frequencies to individual receivers. The power divider provides a minimum of 23 dB of port-to-port isolation preventing signal mixing even at minimal channel separation.

### Product Features

- Rugged constructed components
- Flat gain, high performance Low Noise Amplifier
- High compression point, Low IM generation

