

Wideband RF Isolator

Electrical Specifications

Frequency Band	650-1000 MHz
Bandwidth	Single Frequency
Input Power (Max.)	150 W
Reflected Power (Max.)	75 W
Isolation Ant-Tx (Min.)	30+ dB
Isolator Stage	Single
Load Termination	75 W
Insertion Loss (Max.)	0.30 dB
Return Loss (Min.)	28+ dB
Impedance (Nom.)	50 Ω
RF Connectors	N Female

Mechanical Specifications

Finish	Nickel
Overall Size (HxWxD)	1.5" x 3.5" x 6.6" (38 x 89 x 168 mm)
Net Weight	1.8 lbs (0.8 kg)
Ship Weight	3 lbs (1.4 kg)

Environmental Specifications

Operating Temp. Range	14 to 140 °F (-10 to +60 °C)
-----------------------	------------------------------



EMR Corp W-Series (Wideband) line of ferrite Isolators/Circulators have excellent narrow band as well as broadband specifications. These isolators maintain low insertion loss with stable operation while providing excellent isolation at 30+ dB for single and 65+ dB for dual units. Wider bandwidths help to facilitate stocking requiring fewer SKU Nos for inventory making the W-Series an ideal choice for distributors.

Product Features

- Available from 30 MHz to 1.3 GHz Bands
- Wider Bandwidths available with changes to specifications.

Mounting Hole Pattern - Circulator

