2308-0/2A

RF Power Divider

Electrical Specifications


Frequency Band	30-700 MHz
Insertion Loss (Max. / Typ.)	9.5 / 9.2 dB
VSWR (Max.)	1.5:1
Isolation Port-to-Port (Min.)	23 dB
Input Power (Max.)	0.5 W (as splitter)
Impedance (Nom.)	50 Ω
RF Connectors	N Female

Mechanical Specifications

Finish	Yellow Chem Film
Overall Size (HxWxD)	1.6" x 8.8" x 6" (41 x 224 x 152 mm)
Net Weight	1.35 lbs (0.6 kg)
Ship Weight	3 lbs (1.4 kg)

Environmental Specifications

Operating Temp. Range	-20 to +50 °C





EMR Power Dividers offer frequency ranges from 30 MHz to 960 MHz with low insertion loss and excellent VSWR. All EMR power dividers are backed by 5-Year Warranty and manufactured in the USA.

Product Features

- Wideband
- High isolation
- Low loss
- 5-Year warranty

All product specifications subject to change without notice.

Copyright © 2026 EMR Corporation. All rights reserved.

17431 N. 25th Avenue Phoenix, Arizona 85023 - Toll Free: (800) 796-2875 - Fax: (623) 582-9499 - Email: sales@emrcorp.com