6554/SBB-3(CT)

Band Pass Cavity Resonator

Electrical Specifications

Frequency Band	375-440 MHz
Attenuation	See response curve
Insertion Loss Range	1.5 - 6.0 dB
VSWR (Max. / Typ.)	1.5:1 / 1.25:1
Input Power (Max.)	150 W
Electrical Length	1/4 λ
Impedance (Nom.)	50 Ω
RF Connectors	N Female

Mechanical Specifications

Finish	Gray Paint
Number of Cavities	3
Cavity Body Dimensions (WxD)	4" x 4" (102 x 102 mm)
Cavity Height w/ Tuning Rod	14-16" (356-406 mm)
Rack Mount	19" EIA
Rack Units	3 RU
Dimensions (H x W x D)	5.25" x 19" x 14-16" (133 x 483 x 356-406 mm)
Net Weight	15 lbs (6.8 kg)
Ship Weight	22 lbs (10 kg)

Environmental Specifications

Operating Temp. Range	-22 to 140 °F (-30 to +60 °C)



EMR Band Pass Cavities are 1/4 wavelength, high Q cavity filters with excellent selectivity. Bandpass cavities reject frequencies outside of a narrow pass band. These cavities may be factory tuned to specific frequency and are field tunable. Multiple cavities may be connected for greater selectivity with minimal insertion loss and wider pass bandwidths. Multi-cavity configurations come standard with 19 inch EIA rack mounting bars or panel with chassis tray.

Product Features

- Excellent Frequency Stability
- High-Q Square Cavities
- Low Insertion Loss
- 5 Year Warranty



All product specifications subject to change without notice.

Copyright © 2026 EMR Corporation. All rights reserved.

17431 N. 25th Avenue Phoenix, Arizona 85023 - Toll Free: (800) 796-2875 - Fax: (623) 582-9499 - Email: sales@emrcorp.com